

IN THE CLAIMS

Kindly cancel Claims 41 and 62 without prejudice and with right of re-entry into this application or any other appropriate application. Kindly amend Claims 1-40, 42-49, 52, 57-58, 61, 64-65, and 69, and add new Claims 70-71 as follows.

1(currently amended). A ~~temporary~~ door jamb assembly guard adapted and configured to be installed over, ~~and to temporarily protect,~~ a door jamb assembly ~~during a period when such door jamb assembly is susceptible to an elevated level of risk of damage,~~ such door jamb assembly comprising a door jamb, and an outer trim element joined with such door jamb, such outer trim element and such door jamb defining first (54) and second (55) outer corners facing generally outwardly of a building into which said door jamb assembly may be installed ~~an interior corner,~~ such door jamb assembly having an inner-facing surface defining a door opening, a door-arresting surface, and an outer surface facing away from such door-arresting surface, such inner-facing surface extending from such door-arresting surface to such outer surface, said ~~temporary~~ door jamb assembly guard comprising:

- (a) a central section which overlies the inner-facing surface of such door jamb assembly, said central section having a first door side, and a second opposing side displaced from the door side;
- (b) a door leg section, connected to said central section at said first door side;  
and
- (c) a third ~~an outer leg~~ section, directly or indirectly connected to said central section at said second side facing away from such door opening,

said ~~temporary~~ door jamb assembly guard defining a shock absorber overlying such corners (54, 55), whereby such corners (54, 55) are underlying corners, and wherein said shock absorber transfers forces away from such underlying corners, ~~an element of said shock absorber being adapted and configured to extend between such trim element and such door jamb and to be spaced from such interior corner.~~

2(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 1 wherein said guard can be installed on a door jamb assembly, and wherein a conventional door slab, mounted to such door jamb assembly, can be closed and opened with said guard so installed, without interfering with such operation of such door.

3(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 1 wherein said guard is designed and configured to fit over and protect an outer trim element as part of such door jamb assembly.

4(currently amended). A ~~temporary~~ door jamb assembly guard ~~as in Claim 1,~~ adapted and configured to be installed over a door jamb assembly, such door jamb assembly comprising a door jamb, and an outer trim element joined with such door jamb, such outer trim element and such door jamb defining an interior corner, such door jamb having an inner-facing surface defining a door opening, a door-arresting surface, and an outer surface facing away from such door-arresting surface, such inner-facing surface extending from such door-arresting surface to such outer surface, said door jamb assembly guard comprising:

- (a) a central section which overlies the inner-facing surface of such door jamb assembly, said central section having a first door side, and a second opposing side displaced from the door side;

(b) a door leg section, connected to said central section at said first door side;  
and

(c) an third section, directly or indirectly connected to said central section at said  
second side facing away from such door opening,

said temporary door jamb assembly guard defining a shock absorber, an element of said  
shock absorber being adapted and configured to extend between such trim element and  
such door jamb and to be spaced from such interior corner,

said ~~third~~ outer leg section comprising, in at least partial definition of said shock absorber,  
an interface member connected to said central section at said second side facing away  
from such door, said interface member being sized and configured to extend at a  
transverse angle to said central section, said interface member being arranged and  
configured such that said interface member can extend over, and overlie, at least a portion  
of such outer surface of such door jamb assembly, said ~~third~~ outer leg section further  
comprising a resiliently cushioning nose member extending outwardly in front of said  
interface member, a cavity optionally being defined between said interface member and  
said resiliently cushioning nose member.

5(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 1, said  
door jamb assembly guard being adapted and configured to be installed over a door jamb  
assembly, such door jamb assembly comprising a door jamb, and an outer trim element  
joined with such door jamb, such outer trim element and such door jamb defining an  
interior corner, such door jamb having an inner-facing surface defining a door opening, a  
door-arresting surface, and an outer surface facing away from such door-arresting surface,  
such inner-facing surface extending from such door-arresting surface to such outer  
surface, said door jamb assembly guard comprising:

- (a) a central section which overlies the inner-facing surface of such door jamb assembly, said central section having a first door side, and a second opposing side displaced from the door side;
- (b) a door leg section, connected to said central section at said first door side;  
and
- (c) an third section, directly or indirectly connected to said central section at said second side facing away from such door opening,

said temporary door jamb assembly guard defining a shock absorber, an element of said shock absorber being adapted and configured to extend between such trim element and such door jamb and to be spaced from such interior corner,

and wherein said door jamb assembly guard covers less than the entirety of a width of the inner-facing surface of a such door jamb assembly for which said guard has been designed and configured.

6(currently amended). A ~~temporary~~ door jamb assembly guard as in ~~Claim 1~~, said door jamb assembly guard being adapted and configured to be installed over a door jamb assembly, such door jamb assembly comprising a door jamb, and an outer trim element joined with such door jamb, such outer trim element and such door jamb defining an interior corner, such door jamb having an inner-facing surface defining a door opening, a door-arresting surface, and an outer surface facing away from such door-arresting surface, such inner-facing surface extending from such door-arresting surface to such outer surface, said door jamb assembly guard comprising:

- (a) a central section which overlies the inner-facing surface of such door jamb assembly, said central section having a first door side, and a second opposing side displaced from the door side;

- (b) a door leg section, connected to said central section at said first door side;  
and
- (c) an third section, directly or indirectly connected to said central section at said  
second side facing away from such door opening,

said temporary door jamb assembly guard defining a shock absorber, an element of said  
shock absorber being adapted and configured to extend between such trim element and  
such door jamb and to be spaced from such interior corner,

further comprising a cover tab (92), extending from a distal end (88) of said third outer-leg section, and adapted to extend over an outer face (94) of a trim element of such jamb assembly, with a line of weakness in ~~at the distal end (88)~~ of the third outer-leg section.

7(currently amended). A temporary door jamb assembly guard as in Claim 6 4, ~~further comprising a cover tab extending from a distal end of said outer leg section, and adapted to extend over an outer face (94) of a trim element of such jamb assembly, with a~~ the line of weakness in said third section being located at a locus overlying an outer surface (38) of a such trim element adjacent, ~~but displaced from, distal end (88) of said~~ outer leg section.

8(currently amended). A temporary door jamb assembly guard ~~as in Claim 1,~~ said door jamb assembly guard being adapted and configured to be installed over a door jamb assembly, such door jamb assembly comprising a door jamb, and an outer trim element joined with such door jamb, such outer trim element and such door jamb defining an interior corner, such door jamb having an inner-facing surface defining a door opening, a door-arresting surface, and an outer surface facing away from such door-arresting surface,

such inner-facing surface extending from such door-arresting surface to such outer surface, said door jamb assembly guard comprising:

- (a) a central section which overlies the inner-facing surface of such door jamb assembly, said central section having a first door side, and a second opposing side displaced from the door side;
- (b) a door leg section, connected to said central section at said first door side; and
- (c) an third section, directly or indirectly connected to said central section at said second side facing away from such door opening,

said temporary door jamb assembly guard defining a shock absorber, an element of said shock absorber being adapted and configured to extend between such trim element and such door jamb and to be spaced from such interior corner,

said third ~~outer leg~~ section extending in an arcuate outer surface to an under-curved cushioning distal end overlying an outer surface (38) of such outer trim element.

9(currently amended). A ~~temporary~~ door jamb assembly guard as in ~~Claim 1~~, said door jamb assembly guard being adapted and configured to be installed over a door jamb assembly, such door jamb assembly comprising a door jamb, and an outer trim element joined with such door jamb, such outer trim element and such door jamb defining an interior corner, such door jamb having an inner-facing surface defining a door opening, a door-arresting surface, and an outer surface facing away from such door-arresting surface, such inner-facing surface extending from such door-arresting surface to such outer surface, said door jamb assembly guard comprising:

- (a) a central section which overlies the inner-facing surface of such door jamb assembly, said central section having a first door side, and a second opposing side displaced from the door side;
- (b) a door leg section, connected to said central section at said first door side;  
and
- (c) an third section, directly or indirectly connected to said central section at said second side facing away from such door opening,

said temporary door jamb assembly guard defining a shock absorber, an element of said shock absorber being adapted and configured to extend between such trim element and such door jamb and to be spaced from such interior corner,

said ~~third~~ outer leg section comprising a separate cover tab element (92) adapted to cover an outer face (94) of such a trim element ~~of such door jamb assembly.~~

10(currently amended). A temporary door jamb assembly guard as in Claim 4, said door jamb assembly guard being adapted and configured to be installed over a door jamb assembly, such door jamb assembly comprising a door jamb, and an outer trim element joined with such door jamb, such outer trim element and such door jamb defining an interior corner, such door jamb having an inner-facing surface defining a door opening, a door-arresting surface, and an outer surface facing away from such door-arresting surface, such inner-facing surface extending from such door-arresting surface to such outer surface, said door jamb assembly guard comprising:

- (a) a central section which overlies the inner-facing surface of such door jamb assembly, said central section having a first door side, and a second opposing side displaced from the door side;

(b) a door leg section, connected to said central section at said first door side;  
and

(c) an third section, directly or indirectly connected to said central section at said  
second side facing away from such door opening,

said temporary door jamb assembly guard defining a shock absorber, an element of said  
shock absorber being adapted and configured to extend between such trim element and  
such door jamb and to be spaced from such interior corner,

said third section ~~guard~~ comprising a first ~~outer~~ leg member (52A), and a second ~~outer~~ leg member (52B) attached to the first outer leg member at a locus displaced from a distal edge (64A) of said first outer leg member.

11(currently amended). A ~~temporary~~ door jamb assembly guard ~~as in Claim 1,~~ said  
door jamb assembly guard being adapted and configured to be installed over a door jamb  
assembly, such door jamb assembly comprising a door jamb, and an outer trim element  
joined with such door jamb, such outer trim element and such door jamb defining an  
interior corner, such door jamb having an inner-facing surface defining a door opening, a  
door-arresting surface, and an outer surface facing away from such door-arresting surface,  
such inner-facing surface extending from such door-arresting surface to such outer  
surface, said door jamb assembly guard comprising:

(a) a central section which overlies the inner-facing surface of such door jamb  
assembly, said central section having a first door side, and a second  
opposing side displaced from the door side;

(b) a door leg section, connected to said central section at said first door side;  
and



(c) an third section, directly or indirectly connected to said central section at said second side facing away from such door opening,

said temporary door jamb assembly guard defining a shock absorber, an element of said shock absorber being adapted and configured to extend between such trim element and such door jamb and to be spaced from such interior corner

said third ~~door-leg~~ section being designed and configured to fit, on a correspondingly configured door jamb assembly, between such door-arresting surface and a weather strip element mounted proximate such door arresting surface.

12(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 1, said central section comprising inner and outer section elements, for adjusting said jamb assembly guard according to thickness of a jamb assembly between such door-arresting surface and such outer surface, said inner and outer central section elements interlocking with each other to establish an adjusted width of said central section corresponding to such thickness of such jamb assembly, said outer ~~leg~~ section element being disposed relatively inwardly of such door opening and interfacing with such door-arresting surface, said inner and outer section elements ~~sections~~ being slidably engageable with each other to cause the inner and outer sections to grippingly engage such door-arresting surface and such outer surface of such jamb assembly, thus to custom adjust width of said central section of said guard to fit such thickness of such respective jamb assembly.

13(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 1, ~~said element of said shock absorber~~ further comprising a transition section between said central section and said third ~~outer-leg~~ section.

14(currently amended). A temporary door jamb assembly guard as in Claim 1, said door jamb assembly guard being adapted and configured to be installed over a door jamb assembly, such door jamb assembly comprising a door jamb, and an outer trim element joined with such jamb, such outer trim element and such door jamb defining an interior corner, such door jamb having an inner-facing surface defining a door opening, a door-arresting surface, and an outer surface facing away from such door-arresting surface, such inner-facing surface extending from such door-arresting surface to such outer surface, said door jamb assembly guard comprising:

- (a) a central section which overlies the inner-facing surface of such door jamb assembly, said central section having a first door side, and a second opposing side displaced from the door side;
- (b) a door leg section, connected to said central section at said first door side;  
and
- (c) an third section, directly or indirectly connected to said central section at said second side facing away from such door opening,

said temporary door jamb assembly guard defining a shock absorber, an element of said shock absorber being adapted and configured to extend between such trim element and such door jamb and to be spaced from such interior corner,

and wherein said central section further comprises a release ridge (114) extending along a length thereof, which release ridge is displaced from an underlying jamb by a distance (D1) greater than a base distance (D2) by which a remainder of said central section is displaced from such jamb.

15(currently amended). A temporary door jamb assembly guard as in Claim 4, said door jamb assembly guard being adapted and configured to be installed over a door jamb

assembly, such door jamb assembly comprising a door jamb, and an outer trim element joined with such door jamb, such outer trim element and such door jamb defining an interior corner, such door jamb having an inner-facing surface defining a door opening, a door-arresting surface, and an outer surface facing away from such door-arresting surface, such inner-facing surface extending from such door-arresting surface to such outer surface, said door jamb assembly guard comprising:

- (a) a central section which overlies the inner-facing surface of such door jamb assembly, said central section having a first door side, and a second opposing side displaced from the door side;
- (b) a door leg section, connected to said central section at said first door side;  
and
- (c) an third section, directly or indirectly connected to said central section at said second side facing away from such door opening,

said temporary door jamb assembly guard defining a shock absorber, an element of said shock absorber being adapted and configured to extend between such trim element and such door jamb and to be spaced from such interior corner,

said central section comprising a line of weakness extending along a length of said central section, wherein the line of weakness defines separable inner and outer separable pieces, and facilitates separating said guard into inner (36IN) and outer (36OUT) separate pieces.

16(currently amended). A temporary door jamb assembly guard as in Claim 15, further comprising affixing a structure on at least one of the inner and outer separable pieces prior to separation at the line of weakness, adapted to affix the inner and outer separate pieces to each other in overlapping relationship.

17(currently amended). A temporary door jamb assembly guard having a length, and being adapted and configured to be installed over, ~~and to temporarily protect,~~ a door jamb assembly ~~during a period when such door jamb assembly is susceptible to an elevated level of risk of damage,~~ such door jamb assembly comprising a door jamb, an outer trim element joined with such door jamb, such outer trim element and such door jamb defining an interior corner, such door jamb assembly having an inner-facing surface defining a door opening, a door-arresting surface, and an outer surface facing away from such door-arresting surface, such inner-facing surface extending from such door-arresting surface to such outer surface, said ~~temporary~~ door jamb assembly guard comprising:

- (a) a central section which overlies the inner-facing surface of such door jamb assembly, said central section having a first door side, and a second opposing side displaced from such door side;
- (b) a door leg section, connected to said central section at said first door side and sized and configured to extend at a transverse angle to said central section along such door-arresting surface of said door jamb assembly; and
- (c) an third ~~outer-leg~~ section, directly or indirectly connected to said central section at said second side facing away from such door opening, said third ~~outer-leg~~ section being sized and configured to extend at a transverse angle to said central section,

the second side of said central section of said door frame guard being arranged and configured such that the third section, connected thereto, can be disposed against a such ~~the outer~~ surface of such door jamb assembly, such that said third ~~outer-leg~~ section can extend over, and overlie, at least a portion of such ~~outer~~ surface of such door jamb assembly, said ~~temporary~~ door jamb assembly guard defining a shock absorber, an element of said shock absorber being adapted and configured to protect at least one of ~~extend between~~ such trim element and such door jamb and to be spaced from such interior

corner, said guard defining a terminal edge thereof which does not extend substantially beyond the door leg section.

18(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 17 wherein said guard can be installed on a door jamb assembly, and wherein a respective conventional door mounted to such door jamb assembly can be closed with said guard so installed, without interfering with operation of such door.

19(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 17 wherein said guard is designed and configured to fit over and protect such an outer trim element as part of such door jamb assembly.

20(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 17, said door leg section having a first length between said first door-facing side of said central section and an opposing distal edge of said door leg section, said third section ~~outer leg~~ having a second length, substantially greater than the first length, between said second side of said central section and an opposing distal edge of said third ~~outer leg~~ section.

21(currently amended). A ~~temporary~~ door jamb assembly guard ~~as in Claim 17,~~ having a length, and being adapted and configured to be installed over a door jamb assembly, such door jamb assembly comprising a door jamb, an outer trim element joined with such door jamb, such outer trim element and such door jamb defining an interior corner, such door jamb having an inner-facing surface defining a door opening, a door-arresting surface, and an outer surface facing away from such door-arresting surface, such inner-facing surface extending from such door-arresting surface to such outer surface, said door jamb assembly guard comprising:

- (a) a central section which overlies the inner-facing surface of such door jamb assembly, said central section having a first door side, and a second opposing side displaced from such door side;
- (b) a door leg section, connected to said central section at said first door side and sized and configured to extend at a transverse angle to said central section along such door-arresting surface of said door jamb assembly; and
- (c) an third section, directly or indirectly connected to said central section at said second side facing away from such door opening, said third section being sized and configured to extend at a transverse angle to said central section,

the second side of said central section of said door frame guard being arranged and configured such that the third section, connected thereto, can be disposed against a such surface of such door jamb assembly, such that said third section can extend over, and overlie, at least a portion of such surface of such door jamb assembly, said door jamb assembly guard defining a shock absorber, an element of said shock absorber being adapted and configured to protect at least one of such trim element and such door jamb and to be spaced from such interior corner, said guard defining a terminal edge thereof which does not extend substantially beyond the door leg section,

said ~~third~~ outer-leg section comprising, in at least partial definition of said shock absorber, an interface member, sized and configured to extend at a transverse angle to said central section, said interface member being arranged and configured such that said interface member can extend over, and overlie, at least a portion of such outer surface of such door jamb assembly, said ~~third~~ outer-leg section further comprising a resiliently cushioning nose member extending outwardly in front of said interface member, a cavity optionally being defined between said interface member and said resiliently cushioning nose member.

22(currently amended). A temporary door jamb assembly guard as in Claim 17 wherein said door jamb assembly guard covers less than the entirety of a width of the inner-facing surface of a such door jamb assembly for which said guard has been designed and configured.

23(currently amended). A temporary door jamb assembly guard as in Claim 17, said element of said shock absorber comprising a transition section between said central section and said outer leg section, said transition section comprising a contact web (83) overlying at least one transfer web (86A, 86B).

24(currently amended). A temporary door jamb assembly guard as in Claim 17, said central section comprising a line of weakness extending along a length of said central section, wherein the line of weakness defines inner and outer separable pieces, and facilitates separating said guard into inner (36IN) and outer (36OUT) separate pieces.

25(currently amended). A temporary door jamb assembly guard as in Claim 24, further comprising affixing structure on at least one of the inner and outer separable pieces prior to separation at the line of weakness, adapted to affix the inner and outer separate pieces to each other in overlapping relationship.

26(currently amended). A temporary door jamb assembly guard for installation over, and for temporarily protecting, a door jamb assembly ~~during a period when such door jamb assembly is susceptible to an elevated risk of damage~~, such door jamb assembly having an inner-facing surface defining a door opening, a door-arresting surface, and an outer surface facing away from such door-arresting surface, such inner-facing surface extending from such door-arresting surface to such outer surface, said temporary door jamb assembly guard comprising:

- (a) a central section which can overlie the inner-facing surface of such door jamb assembly, said central section having a first door side, and a second opposing trim side displaced from the door side;
- (b) a door leg section, connected to said central section at said first door side and extending at a transverse angle to said central section so as to extend along such door-arresting surface of said door jamb assembly;
- (c) a third ~~an outer leg~~ section, disposed outwardly of said central section at said second side facing away from such door opening, and disposed away from such wall, said third ~~outer leg~~ section extending at a transverse angle to said central section so as to extend over, and overlie, at least a portion of such outer surface of such door jamb assembly; and
- (d) a transition section between said central section and said third ~~outer leg~~ section, said transition section comprising an overlying contact structure directly interfacing with objects which impact on said transition element, and underlying support structure adapted and configured to interface with one or more underlying surfaces of such jamb assembly, said transition section being effective to absorb and distribute forces imposed thereon so as to attenuate damage to such jamb assembly.

27(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 26 wherein said guard can be installed on a door jamb assembly, and wherein a respective conventional door mounted to such door jamb assembly can be closed with said guard so installed, without interfering with operation of such door.



28(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 26 wherein said guard is designed and configured to fit over and protect an outer trim element as part of such door jamb assembly.

29(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 26 wherein said door jamb assembly guard covers less than the entirety of a width of the inner-facing surface of a such door jamb assembly for which said guard has been designed and configured.

30(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 26 wherein said door leg section terminates at a distal edge thereof comprising a distal edge of said guard, and consistent with termination in the vicinity of, and protecting, such door arresting surface.

31(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 26, further comprising a cover tab, extending from a distal end (88) of said outer leg section, and adapted to extend over an outer face (94) of a trim element of such jamb assembly, with a line of weakness at the distal end (88) of the outer leg section.

32(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 26, further comprising a cover tab extending from a distal end of said third ~~outer leg~~ section, and adapted to extend over an outer face (94) of a trim element of such jamb assembly, and ~~with~~ a line of weakness at a locus overlying an outer surface (38) of a such trim element adjacent, but displaced from, distal end (88) of said third ~~outer leg~~ section.

33(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 26, further comprising a flex joint in said third ~~outer-leg~~ section, operative for rotating a distal edge of said third ~~outer-leg~~ section away from an underlying such door jamb assembly.

34(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 26, said contact structure comprising a contact web (83) extending between first and second sides thereof at said third ~~outer-leg~~ section and said central section, said underlying support structure comprising at least one transfer web, extending from one of said first and second sides of said contact structure in a direction along at least one of (i) a surface of a trim element or (ii) an outer surface of such jamb.

35(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 26 wherein said contact structure comprises a contact web (83), and wherein said underlying support structure comprises a transfer web (86B) extending from said contact web (83) along an outer surface (26) of such door jamb assembly to a locus proximate an intersection of such outer face (26) and an adjoining surface (87) of a trim element.

36(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 26, said underlying support structure of said transition section being adapted and configured to reside in a cavity defined between said contact structure, an inner facing surface (87) of such trim element, and an outer surface (26) of such jamb, and to transfer forces from said contact structure to underlying surfaces of such trim element and such jamb at locations away from outer corners (54, 55) of such trim element and such jamb.

37(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 26, said underlying support structure comprising transfer webs connected to said contact structure and to each other to define a cavity between said transfer webs and said contact

structure, and further comprising support webs (112) extending between said contact structure and at least one of said transfer webs.

38(currently amended). A temporary door jamb assembly guard as in Claim 26, said central section comprising a line of weakness extending along a length of said central section, wherein the line of weakness defines separable inner and outer pieces of said guard, and facilitates separating said guard into inner (36IN) and outer (36OUT) separate pieces.

39(currently amended). A temporary door jamb assembly guard as in Claim 38, further comprising affixing structure on at least one of the inner and outer separable pieces prior to separation at the line of weakness, adapted to affix the inner and outer separate pieces to each other in overlapping relationship.

40(currently amended). A temporary door jamb assembly guard for installation over, and for temporarily protecting, a door jamb assembly during a period when such door jamb assembly is susceptible to an elevated level of risk of damage, such door jamb assembly having an inner-facing surface defining a door opening, a door-arresting surface, and an outer surface facing away from such door-arresting surface, such inner-facing surface extending from such door-arresting surface to such outer surface, said temporary door jamb assembly guard comprising:

- (a) a central section which overlies the inner-facing surface of such door jamb assembly, said central section having a first door side, and a second opposing side facing away from such door side;

- (b) a door leg section, connected to said central section at said first door side and sized and configured to extend at a transverse angle to said central section along such door-arresting surface of such door jamb assembly; and
- (c) a third an outer leg section directly or indirectly connected to said central section at said second side facing away from such door opening, said third outer leg section at least in part defining a resiliently cushioning nose member,

the door jamb assembly defining first (54) and second (55) outer corners, and an inwardly directed corner disposed generally between the first and second outer corners, said nose member transferring and/or distributing forces, imposed on said nose member, away from such corners (54, 55).

41(cancelled).

42(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 40 wherein said guard can be installed on a door jamb assembly, and wherein a conventional door mounted to such door jamb assembly can be closed with said guard so installed, without interfering with operation of such door.

43(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 40 wherein said guard is designed and configured to fit over and protect at least part of an outer trim element as part of such door jamb assembly.

44(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 40, said door leg section having a first length between said central section and an opposing

distal edge of said door leg section, said third outer-leg section having a second length, substantially greater than the first length, between said second side of said central section and an opposing distal edge of said third outer-leg section.

45(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 40 wherein said door jamb assembly guard covers less than the entirety of a width of the inner-facing surface of a such door jamb assembly for which said guard has been designed and configured.

46(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 40, said resiliently cushioning nose member comprising a transition section between said central section and said third outer-leg section.

47(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 40, said central section comprising a line of weakness extending along a length of said central section, wherein the line of weakness defines inner and outer separable pieces of said guard, and facilitates separating said guard into inner (36IN) and outer (36OUT) separate pieces.

48(currently amended). A ~~temporary~~ door jamb assembly guard as in Claim 47, further comprising affixing structure on at least one of the inner and outer separable pieces prior to separation at the line of weakness, adapted to affix the inner and outer separate pieces to each other in overlapping relationship.

49(currently amended). In combination, a door jamb assembly defining a door opening, and a ~~removable~~ guard mounted over and overlying at least a portion of said door jamb assembly, the combination comprising:

- (a) said door jamb assembly having a door jamb, and an outer trim element joined with the door jamb, said door jamb comprising an inner-facing surface facing into the door opening, a door-arresting surface, and an outer surface facing away from the door-arresting surface ~~and away from a building in which said door jamb assembly may be installed~~, the inner-facing surface extending from the door-arresting surface to the outer surface, said outer trim element and such door jamb defining first and second outer corners (54, 55) and an interior corner between said outer corners; and
- (b) said ~~removable~~ guard protecting said door jamb assembly from incidental damage, and comprising
  - (i) a central section overlying the inner-facing surface of the door jamb assembly, said central section having a first door side, and a second opposing side displaced from the door side, and
  - (ii) a third ~~an outer-leg~~ section, directly or indirectly connected to said central section at said second side, and extending away from the door opening, said third ~~outer-leg~~ section extending at a transverse angle to said central section, said third ~~outer-leg~~ section being disposed against, and protecting, the outer surface of the door jamb assembly,

said ~~removable~~ guard defining a shock absorber adjacent the joiner of the door jamb and the trim element, at least a portion of said shock absorber being spaced from such door jamb and such trim element, and protecting at least one of such door jamb and such trim element proximate the outer corners (54, 55), so as to transfer forces away from the outer corners (54, 55), thereby to substantially reduce damage to said jamb assembly such interior corner.

50. (original) A combination as in Claim 49 wherein a conventional door, mounted to said door jamb assembly, can be closed with said guard so installed, without interfering with operation of such door.

51. (original) A combination as in Claim 49 wherein said guard overlies and protects a brick mold as part of said door jamb assembly.

52(currently amended). A combination as in Claim 49, said third ~~outer-leg~~ section comprising an interface member sized and configured to extend at a transverse angle to said central section, the second side of said central section of said door frame guard being arranged and configured such that said interface member can extend over, and overlie, at least a portion of the outer surface of the door jamb assembly, said third ~~outer-leg~~ section further comprising a resiliently cushioning nose member extending outwardly in front of said interface member, a cavity being optionally defined between said interface member and said resiliently cushioning nose member.

53(original). A combination as in Claim 49 wherein said guard covers less than the entirety of a width of the inner-facing surface of a said door jamb assembly.

54(original). A combination as in Claim 49, including weather stripping adjacent the door-arresting surface, said door leg section being disposed between the door-arresting surface and said weather stripping, without interfering with routine mounting, or routine operation, of the weather stripping.

55(previously presented). A combination as in Claim 49, said shock absorber comprising a transition section between said central section and said outer leg section.

56(original). A combination as in Claim 49, said guard comprising inner (36IN) and outer (36OUT) separate pieces, overlapping each other at said central section, and secured to each other.

57(currently amended). A method of protecting a door jamb assembly which defines a doorway opening, from incidental damage during a construction project which is associated with a building, and which has a beginning and an end period~~when the door jamb assembly is susceptible to an elevated level of risk of damage~~, the door jamb assembly comprising left and right upstanding jamb assembly elements, and optionally an upper jamb assembly element extending between the left and right upstanding jamb assembly elements, each such jamb assembly element having an inner-facing surface facing into the doorway opening, a door-arresting surface, and an outer surface facing away from the door-arresting surface, the inner facing surface extending from the door-arresting surface to the outer surface, the door jamb assembly defining first (54) and second (55) outer corners ~~facing generally outwardly of a building into which the door jamb assembly may be installed~~, and an inwardly directed corner disposed generally between the first and second outer corners, the method comprising:

- (a) early in the construction project, ~~removably~~ installing, on one or more of the jamb assembly elements, a removable jamb assembly guard, the jamb assembly guard comprising
  - (i) a central section which overlies the inner-facing surface of the door jamb assembly, and which has a first door side, and a second opposing side displaced from the door side, and
  - (ii) a third ~~an outer leg~~ section, connected directly or indirectly to the central section at the second side displaced from the doorway



opening, the third ~~outer-leg~~ section extending at a transverse angle to the central section,

the third ~~outer-leg~~ section of the guard thus being disposed against the ~~outer surface of the~~ door jamb assembly such that the third ~~outer-leg~~ section extends over, and overlies, at least a portion of the ~~outer surface of the~~ door jamb assembly,

the outer corners (54, 55) underlying the jamb assembly guard,

the jamb assembly guard defining a shock absorber which extends generally between the underlying outer corners (54, 55), and which transfers forces away from the underlying corners (54, 55); and

(b) toward the end of the construction project, removing the jamb assembly guard from the door jamb assembly at least a portion of said shock absorber, between the outer corners, being spaced from the interior corner.

58(currently amended). A method as in Claim 57, further comprising, early in the construction project, installing a temporary door slab in the doorway and, toward the end of the construction project, replacing the temporary door slab with a permanent door slab wherein the guard is mounted and held to the jamb assembly by friction and/or temporary tab interaction with the jamb assembly.

59(original). A method as in Claim 57, including installing the guard on the jamb assembly in combination with a door slab being installed on the jamb assembly, and including closing the door slab, thus to close the door opening, with the guard so installed and without interference between operation of the door slab and the guard.

60. (cancelled).

61(currently amended). A method as in Claim 57, the central section comprising inner and outer section elements, for interlocking with each other thereby to establish an adjusted width of the central section, the method comprising placing the guard over the jamb assembly with the central section in surface-to-surface contact with the inner-facing surface of the jamb assembly, the outer leg section element being disposed relatively outwardly of the doorway opening, the inner door-leg section element being disposed at the door-arresting surface, the method further comprising urging the inner and outer section elements toward each other, thus slidably engaging the inner and outer sections with each other and causing the inner and outer sections to grippingly engage the door-arresting surface of the jamb assembly and the outer surface of the jamb assembly, thus to custom adjust the guard to the respective jamb assembly.

62-63(cancelled).

64(currently amended). A method as in Claim 57, the shock absorber comprising a transition section between the central section and the third outer-leg section such that the transition section protects a corner of a jamb, on the jamb assembly, which faces inwardly of the doorway and outwardly of the building, as well as a corner of a trim element which is part of the jamb assembly, and which corner of the trim element also faces inwardly of the doorway and outwardly of the building, the transition section comprising a contact web (83) and at least one underlying transfer web (86A, 86B).

65(currently amended). A method as in Claim 57, the method further comprising separating the guard into separate inner and outer pieces, at the central section, installing

the inner and outer pieces on one of the jamb assembly elements, with elements of the central section overlapping each other over an inner facing surface of the respective jamb assembly element so as to form respective inner and outer surfaces of an overlap area of the central section, and affixing the overlapped central section elements to each other so as to maintain the overlapped elements in overlapping relationship, and so as to hold the guard on the jamb assembly.

66(original). A method as in Claim 65, further comprising mounting the combination of the jamb assembly and the guard in a doorway opening in a building, thus controlling access to the building while protecting the door jamb assembly from incidental damage.

67(previously presented). A temporary door jamb assembly as in Claim 1 wherein an element of said shock absorber is adapted and configured to be spaced from, and to extend over, at least a portion of such trim element and a portion of such door jamb.

68(previously presented). A temporary door jamb assembly as in Claim 17 wherein an element of said shock absorber is adapted and configured to be spaced from, and to extend over, at least a portion of such trim element and a portion of such door jamb.

69(currently amended). A temporary door jamb assembly as in Claim 26, such said door jamb assembly defining first and second outer corners (54, 55) facing generally outwardly of a building into which such door jamb assembly may be installed, and an adjacent interior corner, said overlying contact structure being adapted and configured to extend between such outer corners (54, 55) and across, and spaced from, such interior corner.

70(new). A door jamb assembly guard as in Claim 6, the line of weakness being adjacent, but displaced from, distal end (88) of said third section.

71(new). A door jamb assembly guard as in Claim 6, the lie of weakness being at the distal end (88) of the third section.